Designed for Reliability

METEOROLOGY

GENERAL DESCRIPTION

The HyQuest Solutions Tipping Bucket Rain
Gauge is recognised as the world standard for
measuring rainfall and precipitation in remote
and unattended locations. Based on Australian
Bureau of Meteorology specifications, the
gauge offers an integrated syphon mechanism
which delivers high levels of accuracy across a
broad range of rainfall intensities.

The gauge consists of a collector funnel with leaf filter with an outer enclosure complete with quick release fasteners with the base housing the tipping bucket mechanism. The unit includes a dual output 24V DC reed switch with varistor protection as well as dual rainfall discharge outlets for water collection and/or analysis.

Main Features

- World standard 200mm diameter catch
- Accuracy not affected by rainfall intensity
- Long term stable calibration
- Minimal maintenance required
- Used world-wide in a range of hostile environments

Resolution

The following resolutions are available:

- 0.1mm
- 0.2mm
- 0.5mm
- 1.0mm
- 0.01 Inch







Accuracy

0-250mm per hour; +/-2% 250-500mm per hour; +/-3%

Range

700mm per hour.

Enclosure

Powder-coated aluminium

Base

UV resistant plastic

Pivots

Stainless steel rolling bearings on stainless spring axle

Bucket Material

Available in painted brass OR chrome plated ABS

Dimensions 310mm (H)

Mass 2.1kg.

Operating Temperature Range -20°C to +70°C

Humidity

Contact Us

General Enquiries (Australia)

Phone: +61 2 9601 2022

Email: sales@hyquestsolutions.com.au Web: www.hyquestsolutions.com.au

General Enquiries (New Zealand)

Phone: +64 (0) 7 857 0810

Email: sales@hyquestsolutions.co.nz Web: www.hyquestsolutions.co.nz

